TECHNICAL SPECIFICATIONS

Specifications >>>

| Functions | Description |
|------------------------|---|
| Monitoring Units | Wired : Max. 64 units |
| | Wireless : Max. 16 units |
| Supported Device Model | BM3, BM5, (BM3 Lite, BM3 Plus) |
| Network | Wired : LAN |
| | Wireless: W-LAN (communication distance: 30m) |
| View Mode | 2, 4, 8, 16, and 32 Monitors View Mode |
| Patient Data Storage | According to storage amount |
| Alarm | Sound and Display |
| Communication Type | Bi-directional control |
| Reviewer | Alarm, Waveform, Graphic Trend, and Tabular Trend |
| Print and Report | 4 kinds of Report Form : Alarm, Waveform, |
| | Graphic Trend, and Tabular Trend |
| Certificate | C € ₀₁₂₃ |
| HIS/EMR connection | HL7 support |
| Supported Languag | English, Italian, French, Spanish, German, Chinese, |
| | Russian, Polish, Czech, Turkish, Romanian, Portugues, |
| | Bulgarian, Korean |

Configuration >>>

110324-010000 BMCentral System (Wired LAN)

| Order No. | Description | EA |
|---------------|--|----|
| 110324-030000 | Software BMCentral CD | 1 |
| 151900-045300 | Lock Key Central Software (USB Memory) | 1 |
| 152600-023700 | Op Manual/EN/BMCentral | 1 |
| 151900-038900 | Desktop PC (with monitor)-Dell | 1 |
| 152600-020900 | ACC. PC Speaker (Central) | 1 |
| 151900-039100 | HUB 16Port 3COM 16p 3C16470 10/100M | 1 |
| 151900-039700 | Cable LAN 30m | 8 |
| 151900-039800 | Cable LAN 5m | 1 |

110324-020000 BMCentral System (Wireless LAN)

| Order No. | Description | EA |
|---------------|---|----|
| 110324-030000 | Software BMCentral CD | 1 |
| 151900-045300 | Lock Key Central Software (USB Memory) | 1 |
| 152600-023700 | Op Manual/EN/BMCentral | 1 |
| 151900-038900 | Desktop PC(with monitor)-Dell | 1 |
| 152600-020900 | ACC. PC Speaker (Central) | 1 |
| 151900-039300 | Wireless Access Point (WHR-HP-G54) | 1 |
| 151900-039400 | Wireless Ethernet Converter (WLI-TX4-G54HP) | 8 |
| 151600-005000 | Cable BM5 W-LAN 5.0 DC | 8 |
| 152300-010800 | Bracket W-Lan Holder | 8 |

Patient Monitoring Central System

BMCentral

- Monitoring up to 64 beds simultaneously using wired LAN
- Wireless LAN available for monitoring up to 16 beds to 30m
- Bi-directional Control
- Up to 14 languages support
- (Approval
- HIS/EMR connection support by sending HL7 message







South Korea: Bionet co., Ltd. Tel:+82-70-7585-6418(Int'l) +82-2-6292-6483(Domestic) E-mail:sales@BionetUS.com www.BionetUS.com

E-mail:sales@ebionet.com(Int'l) ajy@ebionet.com(Domestic)

Patient Monitoring Central System BMCentral

BMCentral is...


The BMCentral system supports centralized monitoring environments through powerful networking capabilities.

It allows the user to monitor and extract the exact status of several patients simultaneously from one location.

Convenient bi-directional communication allows you admit new patient information, set alarms at either central station or patient monitor.


Easy to use and cost effective expandable system!


- Monitoring 64 beds is available using Wired LAN
- Monitoring 16 beds is available using Wireless LAN
- All BM series can be connected
- Bi-directional communication with Patient Monitors
- HIS connection (Hospital Information System): Sending HL7 message with MFER file







- Automatic connection and arrangement
- Diverse monitoring mode
 - 2,4,8,16 and 32 Channels view mode
 - Large & detail monitoring window
- Parameter, waveform, alarm information are saved
- 4 Kinds of review mode and report form are provided
 - Alarm, Waveform, Graphic trend, Tabular trend







[Wave Review]



[Graphic trend Review]

