

# BM3VET ELITE

## VETERINARY PATIENT MONITOR

bionet

### Physical Specifications

Dimension(mm)	237(H) x 240(W) x 176(D)
Weight(Kg)	3.1
Display	8" Touchscreen
Resolution	800 x 600
Control Keys	Power Key, Rotary Knob, Alarm Key, Printer Key, BP measurement Key, Home Key

#### Trace

Waveforms	Up to 4 - 1CH ECG, SpO <sub>2</sub> , RR or EtCO <sub>2</sub>
Sweep Speed	6.25 mm/sec, 12.5 mm/sec, 25 mm/sec, 50 mm/sec
Species	Feline, Canine, Equine
Patient Type	Dog, Puppy, Cat, Horse

### Parameters and Modules

ECG	3/5 Lead(1CH)
SpO <sub>2</sub>	SpO <sub>2</sub>
NIBP	Bionet
TEMP	1CH
EtCO <sub>2</sub>	Mainstream & Sidestream

#### ECG

ECG Leads	3 Lead: I, II, III 5 Lead: I, II, III, aVR, aVL, aVF, V
Heart Rate	
Range	Dog, Puppy, Cat, Horse : 30 to 300 bpm
Accuracy	±1 bpm or ±1%, whichever is greater
ST Segment Detection Range	-2.0 to 2.0 mV
Arrhythmia Analysis	Asystole, V-Tach, V-Fib
Pacemaker Detection Mode	Indicator on waveform display (user selectable)
Protection	Against electrosurgical interference and defibrillation

#### Respiration

Method	Thoracic impedance
Channel Selection	RA-LL
Measurement Range	5 to 120 bpm
Accuracy	±1 bpm
Apnea Alarm	Yes

#### SpO<sub>2</sub>

Range	0 to 100%
Accuracy*	70 to 100% : ±2 digits 0 to 69% : unspecified
Pulse Rate Range	18 to 450 bpm
Pulse Rate Accuracy	±2 bpm

\* The specified accuracy is the root-mean-square (RMS) difference between the measured values and the reference values.

### Non-Invasive Blood Pressure

Method	Oscillometry with step deflation
Operation Mode	Manual/Automatic/Continuous
Measurement Range	Systolic : 40 to 260 mmHg MAP : 26 to 220 mmHg Diastolic : 20 to 200 mmHg
Accuracy	Mean error : less than ±5 mmHg Standard deviation : less than 8 mmHg

### Temperature

Method	Thermal resistance
Operation Mode	Direct
Measurement Range	0 to 50°C (32 to 122°F)
Accuracy	25 to 50°C : ±0.1°C 0°C to 24°C : ±0.2°C
Compatibility	98ME04GA603 temperature probes

### ETCO<sub>2</sub>(Main/Sidestream)

Measurement Range	0 to 150 mmHg, 0 to 19%
Accuracy	0 to 40mmHg ±2 mmHg, 41 to 70mmHg ±5% of reading 71 to 100mmHg ±8% of reading 101 to 150mmHg ±10% of reading
Respiration Rate	0 to 150 bpm (Mainstream) 2 to 150 bpm (Sidestream)
Respiration Accuracy	±1 bpm

### Environmental Specifications

Temperature	
Operating	5 to 40 °C (41 to 104 °F)
Storage	-20 to 60 °C (-4 to 140 °F)
Humidity	
Operating	30 to 85%
Storage	10 to 95% (Package)
Altitude	
Operating	525 to 795 mmHg (70 to 106 kPa)
Storage	375 to 795 mmHg (50 to 106 kPa)

### Power Specifications

Power Consumption	< 50 W
Line Voltage	100 to 240 VAC
Current	1.5 to 0.75 A
Frequency	50/60 Hz
Battery	Rechargeable Lithium ion 10.8 V 2,150 mAh or 3,250mAh(Standard) /6,500mAh(option)

Interface Specifications

Interface	DC input connector : 18VDC, 2.8A LAN port for transferring data Nurse call system connector 2 USB 2.0 connector HDMI output connector
Data Storage	
Common	168 hrs trends data
Option	20 cases of 10 sec alarm waveform
Indicators	Categorized alarms (3 priority levels), Visual alarm lamp, SpO2 pulse pitch tone, Battery status, External power LED
Network	
Wired	IEEE 802.3
Wireless	IEEE 802.11 (a, b, g, n)
Safety	
Type of Protection	Class I
Ingress Protection	IPX2

Headquarters Bionet Co., Ltd.  
5F, 61 Digital-ro 31-gil, Guro-gu, Seoul, Korea 08375  
TEL. +82 2 6292 6410  
E-Mail. domestic.sales@ebionet.com  
info.sales@ebionet.com (Overseas Sales)