

## Physical Specifications

Dimension(mm)	394(H) x 305(W) x 157(D)
Weight(Kg)	4.1
Display	15.6" Capacitive Touchscreen
Resolution	1366 x 768
Control Keys	Power Key, Trim Knob, Alarm Key, Snapshot Key, NIBP measurement Key
Trace	
Waveforms	Up to 7 - ECG, SpO <sub>2</sub> , RR or EtCO <sub>2</sub> or AG, 4CH IBP
Sweep Speed	6.25 mm/sec, 12.5 mm/sec, 25 mm/sec, 50 mm/sec

## Parameters and Modules

ECG	3 Lead(1CH)
SpO <sub>2</sub>	Bionet SpO <sub>2</sub>
NIBP	SuntechBP
IBP	4CH
TEMP	2CH
Optional	- EtCO <sub>2</sub> Mainstream & Sidestream
	- 7CH ECG, AG(Dual-gas), AG(Anesthesia Gases with Paramount)

### ECG

Method	Meets the requirements of IEC 60601-2-27: 2011 and IEC 60601-2-25: 2011
ECG Leads	3 Lead : 1CH I, II, III 5 Lead : 2/7CH I, II, III, aVR, aVL, aVF, V
Heart Rate	
Range	15 to 350 bpm
Accuracy	±1 bpm or ±1%, whichever is greater
ST Segment Detection Range	-2.0 to 2.0 mV
Protection	Against electrosurgical interference and defibrillation

### Respiration

Method	Thoracic impedance
Channel Selection	RA-LL / RA-LA
Measurement Range	5 to 120 bpm
Accuracy	±1 bpm
Apnea Alarm	Yes

### SpO<sub>2</sub>

Range	0 to 100%
Accuracy*	70 to 100% : ±2 digits 0 to 69% : unspecified
Pulse Rate Range	18 to 450 bpm
Pulse Rate Accuracy	±2 bpm

\* The specified accuracy is the root-mean-square (RMS) difference between the measured values and the reference values.

## Non-Invasive Blood Pressure

Standard	Meets the requirements of ISO 80601-2-30:2018
Method	Oscillometry with step deflation
Operation Mode	Manual/Automatic
Measurement Range	Systolic : 40 to 260 mmHg MAP : 26 to 220 mmHg Diastolic : 20 to 200 mmHg

## Temperature

Standard	Meets the requirements of ISO 80601-2-56:2018
Method	Thermal resistance
Operation Mode	Direct
Measurement Range	0 to 50°C (32 to 122°F)
Accuracy	25 to 45°C : ±0.1°C Below 25°C, above 45°C : ±0.2°C
Compatibility	98ME04GA603 temperature probes

## IBP

Standard	Meets the requirements of IEC 60601-2-34: 2011
Channels	4CH
Measurement Range	-50 to 300 mmHg
Accuracy	±4% of reading or ±4 mmHg, whichever is greater
Pulse Rate Measurement Range	20 to 300 bpm
Zero Balancing	Range : ±200 mmHg Accuracy : ±1 mmHg Drift : ±1 mmHg over 24 hrs
Transducer Sensitivity	5μV/V/mmHg

## ETCO<sub>2</sub>(Main/Side)

Standard	Meets the requirements of ISO 80601-2-55:2018
Measurement Range	0 to 150 mmHg, 0 to 19%
Accuracy	0 to 40 mmHg ±2 mmHg, 41 to 70 mmHg ±5% of reading 71 to 100 mmHg ±8% of reading 101 to 150 mmHg ±10% of reading
Respiration Rate	2 to 150 bpm
Respiration Accuracy	±1 bpm

AG(Dual-gas)		
CO <sub>2</sub>		
Range	0 to 76 mmHg; 0 to 10.1 kPa; 0 to 10% CO <sub>2</sub> STPD (standard temperature and pressure dry)	
Accuracy	± (0.2% vol% + 4% relative)	
N2O Interference	30% N2O increases CO2 reading by 3.25mmHg at 10% CO2	
Anesthetic Agents		
Gases	Isoflurane, Desflurane, Sevoflurane	
Range	Iso. & Sev.: 0 to 6% Des.: 0 to 18%	
Accuracy	± (0.15% vol% + 4% relative)	
Resolution	0.01%	
Respiration		
Range	0 to 150 bpm	
Accuracy	±1 bpm	
Flow Rate		
Range	175 ml/min	
Accuracy	±25ml/min	
AG(Anesthesia Gases with Paramount)		
Standard	Meets the requirements of ISO 80601-2-55:2018	
Technique	Infrared absorption, paramagnetic properties for O <sub>2</sub> monitoring	
Warm-up Time	≤10 min	
Measurement Range	CO <sub>2</sub>	0 to 30%
Range	O <sub>2</sub>	0 to 100%
	N <sub>2</sub> O	0 to 100%
	Des	0 to 30%
	Sev	0 to 30%
	Enf	0 to 30%
	Iso	0 to 30%
	Hal	0 to 30%
	awRR	2 to 100 rpm
	Resolution	CO <sub>2</sub>
	O <sub>2</sub>	1%
	N <sub>2</sub> O	1%
	Des	0.1%
	Sev	0.1%
	Enf	0.1%
	Iso	0.1%
	Hal	0.1%
	awRR	1 rpm

## Environmental Specifications

Temperature	
Operating	5 to 40 °C (41 to 104 °F)
Storage	-20 to 60 °C (-4 to 140 °F)
Humidity	
Operating	30 to 85%
Storage	10 to 95% (Package)
Altitude	
Operating	525 to 795 mmHg (70 to 106 kPa)
Storage	375 to 795 mmHg (50 to 106 kPa)
Power Consumption	
Line Voltage	< 35 W
Current	100 to 240 VAC
Frequency	1.5 to 0.75 A
	50/60 Hz

Battery	Rechargeable Lithium ion 10.8 V 3,250mAh / 6,500mAh
Interface	AC input connector LAN port for transferring data HDMI output connector 2 USB 2.0 connector Printer module connector Paramount module connector
Data Storage	
Common	168 hrs trends data
Option	1,000 alarm events (All numbers and waveforms for a total of 16 sec, 8 sec before and after the event)
Indicators	3 Colors visual alarm lamp, SpO <sub>2</sub> pulse pitch tone, Battery status, External power LED
Network	
Wired	IEEE 802.3
Wireless	IEEE 802.11 (a, b, g, n)
Safety	
Type of Protection	Class I
Ingress Protection	IPX2

## Headquarters Bionet Co., Ltd.

5F, 61 Digital-ro 31-gil, Guro-gu, Seoul, Korea 08375  
TEL. +82 2 6292 6410  
E-Mail. domestic.sales@ebionet.com  
info.sales@ebionet.com